KCI-301

- La unidad de control y la pistola funcionan en conjunto eficientemente.
- Hopper de 40 lt. fácil de limpiar.
- Posibilidad de trabajo en abanico plano o redondo.
- Pistola robusta ultra liviana con controles de simple uso.

Características técnicas:

Peso de la pistola	420 g
Largo de la pistola	330 mm
Voltaje	(AC)220 V
Frecuencia	50~60Hz
Consumo de energía	30w
Voltaje de entrada	(DC)24V
Voltaje de salida	100kV
Máxima salida de corriente	180μA
Polaridad (negativa)	Negativa
Modo de alto voltaje	Dentro de pistola
Máxima capacidad de inyección	650g/Min
Consumo de aire	MAX. 13N㎥/h
Pulsaciones	15~20 clock/sec
Rango de temperaturas	-10~-50℃

Modulo pre programado con 4 configuraciones distintas para una variedad de partes y superficies.

- **Modo complejo**
  Ajusta el voltaje manteniendo la corriente para formas complicadas y esquinas.

- **Modo recubrimiento**
  Ajusta el voltaje y corriente automáticamente para recubrimiento de partes.

- **Modo pulsos**
  Rápidamente recarga el polvo para formas complejas.

Allows user to manually adjust the voltage as needed.

Complex Mode
Adjusts the voltage while holding current when coating complicated shapes and corners

Recoat Mode
Adjusts the voltage and current automatically for recoating of parts

Pulse Mode
Rapidly recharges the powder to coat complex shapes

Flat Mode
Maximizes voltage for superior transfer efficiency when coating flat parts

- **Modo plano**
  Maximiza el voltaje para una superior taza de transferencia cuando se cubren partes planas.