

## INL-Plural Component Equipment DuoMix 333 2:1 Portable System



## INL - DuoMix 333 Interchangeable Ratio Plural Component Spray System



- Mix ratio: 2:1 (3x 99ccm)
- Pressure ratio: 68:1
- Maximum fluid pressure: 6800 psi @ 100 psi in bound air
- Maximum fluid deliver: 3.1 gallons @ 40 cycles per minute
- 4 Wheel Cart, able to be moved via forklift
- Air Maintenance unit, filter, oiler, and regulator with gauge
- Two material high-pressure fluid filters with over-pressure safety system
- Fluid Pressure Gauge for each material pump (total 3)
- Grounding wire kit

## INL-WIWA 72.32 Flushing Pump



- The flush pump is interconnected to allow the operator to flush mixed material from the mix manifold, spray hose, spray gun thru the spray tip once the work is complete or when a work has stopped this period of time must not exceed the pot life time once again flushing is expected
- Ratio 32:1
- Maximum fluid pressure 3712 psi
- Maximum fluid delivery 1.14 gpm. @ 60 cycles per minute

## INL-WIWA Pressure Monitor System for Ratio Control



- Provides the operator with ratio assurance with Automatic Shut Down feature should the material pressures become unbalanced
- Includes contact pressure gauge for catalyst component
- Pneumatic stroke counter

## INL-WIWA Fluid Heaters (1x Resin, 1x ISO)



- 230V, single phase (other ratings available upon request)
- 3500W, 16A
- Thermostat range: 0 - 185°F
- Max. operating pressure: 6615 psi
- Explosion-proof in accordance with EC guideline 94/9/EG as well as the following standards:
  - $\text{Ex}$  II 2G / EEx d IIB 165°C (T3)
- Fluid temperature gauge

### WIWA Remote Mix Manifold with Manual Control



- Capable of blending Base and Catalyst component efficiently.
- Manual On/Off Flow Control Valves for Base and Catalyst to Mix Manifold.
- Manual On/Off Recirculation Valves for Base and Catalyst returning back to supply containers.
- Separate flushing ports for Base and Catalyst ensure maximum cleaning of this area plus the point of material contact in the mix manifold and static mixer.
- Static Mixer Assembly 12" long with Removable 24 Turn Mixing Element,

### WIWA Spray Accessories



- WIWA 500F Spray Gun (Qty. 1)
  - Max. pressure 7350 psi
  - Incl. reversible tip housing
- 50', 3/8" Spray Hose (Qty. 1)
- 3', 1/4" Whip Hose (Qty. 1)

### Electrically Heated Insulated Hose Package (Complete)

