





This paint pump is able to supply one or two Airmix® spray guns meeting the spray painting requirements of main industry. This pump embeded a patented seals for long term usage.

- Perfect Airmix® finish
- Built with minimal parts
- Lowest cost of ownership

ACCELERATOR OF PERFORMANCE







Configuration of the 15C50 Airmix® paint pump

Set-up	Sealing		Fluid inlet			Atomization	Air regulator	Filter pump	
	GT seal	MB-A	fitting	Suction rod	Drain rod	air regulator	Fluid pressure	outlet	Part number
Wall Mounted F1/2	•	-	F 1/2 BSP	-	-	•	•	-	151.143.000
		-	M 26x125	-	-			-	151.143.050
Wall Mounted M26X125 with filter and suction		-		Ø25	•			•	151.143.250
Wall Mounted M26X125 with filter		-		-	•			•	151.143.450

Maintenance kits

Description	Part number
Servicing kit - Motor 420-4	144 130 190
MB-GT cartridge	144.135.205
Piston assembly and MB-GT cartridge	144.135.291

Accessories

Description	Part number
Wall-mounted totem	151.140.240
Stand	151.140.210
Double Post Cart	151.241.000
Gravity Hopper 6 liters	151.140.230
Easyflow suction rod Ø25 plunging tube length 600 mm	149.596.150
Easyflow suction rod Ø25 plunging tube length 1000mm (for 200 liters drums)	149.596.160
Stainless steel drain rod F18 x 125	049.596.000
Fluid filter	155.580.600
Air plate with 2 air regulator	151.140.070

