



ESCARIFICADORAS

HUSQVARNA CP 9

Art.no: 970 80 12-05

Husqvarna CP 9 is a professional floor scarifier designed for high productivity without compromising on transportability, ergonomics or simplicity. This machine is an excellent choice for concrete and steel surface preparation, thick coating removal, texturing, levelling, profiling and creating adhesion profiles. With a 9-inch (225 mm) working width, this robust scarifier is effortless to maintain and quick to decontaminate. Intuitive controls and user-friendly features help operators achieve consistent results with limited training and minimal chance of misuse. Turnaround between jobs is fast with the revolutionary Husqvarna tube refill kit – a patented system featuring pre-filled tooling tubes that refill drum shafts instantly. The machine is also available in petrol and battery versions, which provide the added flexibility of cordless operation. Included: Full drum (with Tacti-Cutter™ Tungsten carbide wheels) Not included: milling cutters, star wheel cutters, edge drum, wall guidance, Elite-Shave™ blades

FEATURES



Easy to use

All users can run the machine with confidence. It features simplified controls, a depth indicator and an LED load indicator that helps operators work at the most productive scarifying depth without overloading the motor.



Fast tool changes

The Husqvarna tube refill kit reduces the time it takes to replace tools to as little as 7.5 minutes and minimises the risk of error. Each kit contains a complete set of numbered tubes pre-loaded with spacers and cutters. The tools can slide smoothly on all at once because the drum shafts have no welded middle flanges blocking the way. This also means tools are spaced evenly from end to end, which creates a consistent scarifying pattern.



Easy to transport

The robust frame folds down to make the machine more compact and protect vital components. Features sensibly placed lifting hooks and strap-down points.



Low cost of ownership and maximum uptime

Because all models share the same mechanical platform and common parts, you can enjoy all the versatility of having a mixed fleet while keeping inventory costs down. Tooling is unified for efficient stock management. The robust, protective frame and heavy duty bearings reduce the need for repairs and help maximise machine uptime.

TECHNICAL DATA HUSQVARNA CP 9

Art.no: 970 80 12-05

HUSQVARNA CP 9

MOTOR

Potencia de salida	3.7 kW
Voltaje	230-250 V
Corriente nominal, A	18.5 A
Fuente de alimentación	Cable

DATOS DEL PRODUCTO

Velocidad de rotación	1,450 rpm
Anchura de trabajo	22.5 cm
Tipo de operación	Empuje manual

DIMENSIONES

Longitud del producto	1,136 mm
Ancho del producto	381 mm
Altura del producto	1,136 mm
Peso	111 kg
Longitud del embalaje	880 mm
Ancho del embalaje	500 mm
Altura del embalaje	1,135 mm
Peso bruto del artículo	133,000 g

NIVEL DE POTENCIA DE SONIDO

Nivel de presión sonora en oído	89 dB(A)
---------------------------------	----------

VIBRACIONES

Vibraciones en manillar	4.1 m/s ²
-------------------------	----------------------



Revisa toda nuestra gama de productos en

www.inl.cl/categoria-producto/construccion/preparacion-de-sustratos/